



SIZE/PART No. (DXT) (mm)	MAX COMPRESSIVE LOAD (kg)	STATIC DEFL (mm)	THREAD SIZE	
			BOLT	NUT
PO 13x13 A	4.5	1.0	M6X1Px13L	M6X1Px4 DEEP
PO 16X15 A	5.6	1.0	M5X0.8Px12L	M5X0.8Px5 DEEP
PO 19X19	A 18	3.0	M6X1Px19L	M6X1Px4 DEEP
	B 25	3.0		
	C 35	3.0		
PO 20x20 C	29	4.0	M6x1Px17L	M6x1Px6 DEEP
PO 20x25	A 6.0	3.0	M6x1Px17L	M6x1Px6 DEEP
	B 8.0	3.0		
	C 11	3.0		
	D 18	4.0		
	E 21	3.0		
PO 25x20	A 30	3.5	M6x1Px13L	M6x1Px6 DEEP
	B 45	3.5		
	C 60	3.5		
PO 25x22 A	50	3.5	M8x1.25Px20L	M8x1.25Px6 DEEP
PO 25x30	A 37	3.0	M8x1.25Px20L	M8x1.25Px6 DEEP
	B 52	3.0		
	C 73	3.0		
PO 30x22 A	64	3.5	M8x1.25Px25L	M8x1.25Px6 DEEP
PO 30X30 A	22	3.0	M8x1.25PX21L	M8x1.25Px6 DEEP
PO 35x25	A 16	1.5	M8x1.25PX38L	M8x1.25Px6 DEEP
	B 21	1.5		
	C 40	1.5		
	D 65	1.5		

SIZE/PART No. (DXT) (mm)	MAX COMPRESSIVE LOAD (kg)	STATIC DEFL (mm)	THREAD SIZE	
			BOLT	NUT
PO 38x25	A 70	4.0	M8x1.25Px17L	M8x1.25PX6 DEEP
	B 110	4.0		
	C 175	4.0		
PO40x28 B	146	4.5	M10x1.5Px25L	M10x1.5Px6 DEEP
PO40x30 B	60	5.0	M8x1.25Px25L	M8x1.25Px6 DEEP
PO40x40	A 43	6.0	M10x1.5Px38L	M10x1.5Px10 DEEP
	B 59	6.0		
	C 82	6.0		
PO50x40	A 65	5.0	M10x1.5Px22L	M10x1.5Px12 DEEP
	B 110	5.0		
	C 150	5.0		
PO50x45 B	106	7.0	M10x1.5Px25L	M10x1.5Px12 DEEP
PO50x50	A 76	7.0	M10x1.5Px22L	M10x1.5Px12 DEEP
	B 100	7.0		
	C 120	7.0		
PO60x60	A 110	8.0	M12X1.75PX27L	M12X1.75PX15 DEEP
	B 150	8.0		
	C 200	8.0		
PO63X36 A	115	5.0	1/2"BSWX33L	1/2"BSWX10 DEEP
PO75X55	A 158	6.0	M12X1.75PX37L	M12X1.75PX15 DEEP
	B 180	6.0		
	C 290	6.0		

METHOD OF ORDERING

PO 38 25 A 2  
D T STIFFNESS TYPE